(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 26 May 2005 (26.05.2005)

PCT

(10) International Publication Number WO 2005/048276 A2

(51) International Patent Classification7: C04B 35/26, G03G 9/00

H01F 1/34,

Kanto Denka Kogyo Co., Ltd., 425, Kanai, Shibukawa-shi, Gunma 3770027 (JP).

(21) International Application Number:

PCT/JP2004/016811

(22) International Filing Date:

5 November 2004 (05.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-382668

12 November 2003 (12.11.2003) TP

2004-264875

13 September 2004 (13.09.2004)

- (71) Applicant (for all designated States except US): KANTO DENKA KOGYO CO., LTD. [JP/JP]; 2-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 1000005 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): IINUMA, Hidehiko [JP/JP]; c/o Matarials for Recording Media Lab., Kanto Denka Kogyo Co., Ltd., 425, Kanai, Shibukawa-shi, Gunma 3770027 (JP). HAYASHI, Masatomo [JP/JP]; c/o Matarials for Recording Media Lab., Kanto Denka Kogyo Co., Ltd., 425, Kanai, Shibukawa-shi, Gunma 3770027 (JP). MATSUURA, Natsuki [JP/JP]; c/o Matarials for Recording Media Lab., Kanto Denka Kogyo Co., Ltd., 425, Kanai, Shibukawa-shi, Gunma 3770027 (JP). OGUMA, Yukinari [JP/JP]; c/o Matarials for Recording Media Lab.,

(74) Agent: OKIMOTO, Kazuaki; YUASA AND HARA, Section 206, New Ohtemachi Bldg., 2-1, Ohtemachi 2-chome, Chiyoda-ku, Tokyo 1000004 (JP).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AN MG-BASED FERRITE, AN ELECTROPHOTOGRAPHIC DEVELOPMENT CARRIER CONTAINING THE FERRITE, AND DEVELOPER CONTAINING THE CARRIER

(57) Abstract: This invention provides an Mg-based ferrite having a high dielectric breakdown voltage and a saturation magnetization suitable for electrophotographic development, a carrier containing the ferrite, and an electrophotographic developer containing the carrier. The Mg-based ferrite material of this invention comprises Li, Na, K, Rb, Cs, Ca, Sr, Ba, Y, La, Ti, Zr, Hf, V, Nb, Ta, Al, Ga, Si, Ge, P, Sb, Bi or a combination thereof. The Mg-based ferrite material has a saturation magnetization of 30 to 80 emu/g, and a dielectric breakdown voltage of 1.5 to 5.0 kV. The Mg-based ferrite material can realize high image quality, and be in compliance with environmental regulations.

